

# Olympia Micro™ *ClimaPlus*™



10

**Year Availability**

4211, 4221, 4231, 4411, 4421, 4742, 4744



OLYMPIA MICRO Panels with *CLIMAPLUS* Superior Performance  
DONN FINELINE DXF Suspension System

**LEED Credits**

Recycled Content: 56%  
*CLIMAPLUS* Superior Performance for Mold/Mildew

MR				EQ		
Waste Reduction <sup>1</sup>	Recycled Content	Regional Materials <sup>2</sup>	Rapidly Renewable Materials	Low-Emitting Materials	Daylight and Views	Acoustical Performance
●	●	●	●	●	●	●

**Features and Benefits**

- Nondirectional pattern reduces installation time and waste.
- Economical, fine-textured panel.
- Excellent light reflectance enhances indirect lighting of a space.
- Available with .60 NRC to assist in addressing HIPAA requirements (excludes items 4750 & 4751).
- *CLIMAPLUS* 30-year lifetime system warranty to withstand conditions up to 104 °F (40 °C)/95% relative humidity without visible sag when used with a *DONN*® brand suspension system.

**Applications**

- Healthcare
- Classrooms
- Hotels
- Reception and lobby areas
- Restaurants
- Retail stores

**Substrate**

- Water-felted mineral fiber



Fine-textured panel

Call 888.874.2450 for samples



White

**30**

Year System Warranty  
 - No visible sag  
 - Mold/mildew protection

UL Classified

Edge	Panel Size	Class	Item No.	NRC	CAC Min.	LR <sup>2</sup>	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew	Recycled Content <sup>4</sup>	Panel Cost	
<b>OLYMPIA MICRO CLIMAPLUS Panels .50 NRC<sup>7</sup></b>	SQ 	2'x2'x5/8"	Class A	<b>4211</b>	.50	30	.87	White	A, B, C	Low		52%	\$\$
		2'x4'x5/8"	Class A	<b>4411</b>	.50	30	.87	White	A, B	Low		52%	\$\$
	SLT 	2'x2'x5/8"	Class A	<b>4221</b>	.50	30	.87	White	D	Low		52%	\$\$
		2'x4'x5/8"	Class A	<b>4421</b>	.50	30	.87	White	D	Low		52%	\$\$
	FLB 	2'x2'x5/8"	Class A	<b>4231</b>	.50	35	.87	White	E, F, G	Low		52%	\$\$
		2'x4'x5/8"	Class A	<b>4431</b>	.50	35	.87	White	E, F, G	Low		52%	\$\$
<b>OLYMPIA MICRO CLIMAPLUS Panels .60 NRC<sup>7</sup></b>	SQ 	2'x2'x3/4"	Class A	<b>4750</b>	.60	33	.87	White	A, B, C			56%	\$\$
		2'x4'x3/4"	Class A	<b>4751</b>	.60	33	.87	White	A, B			56%	\$\$
	SLT 	2'x2'x3/4"	Class A	<b>4752</b>	.60	35	.87	White	D			56%	\$\$
		2'x4'x3/4"	Class A	<b>4753</b>	.60	35	.87	White	D			56%	\$\$
	FLB 	2'x2'x3/4"	Class A	<b>4754</b>	.60	35	.87	White	E, F, G			56%	\$\$
		2'x4'x3/4"	Class A	<b>4755</b>	.60	35	.87	White	E, F, G			56%	\$\$
<b>OLYMPIA MICRO CLIMAPLUS Illusion Two/24 Panels</b> The look of 2'x2' panels	SLT <sup>5</sup> 	2'x4'x3/4"	Class A	<b>4742</b>	.50	35	.87	White	D	Low		52%	\$\$
	ILT <sup>6</sup> 	2'x4'x3/4"	Class A	<b>4744</b>	.50	35	.87	White	E, H	Low		52%	\$\$

**Illusion Two/24**

**Patterns**



**Legend**

**Low Emissions (VOC Class)**

Classified as low-emitting per standards established by the Collaborative for High-Performance Schools (CHPS), following California Specification 01350 testing methods.

**CLIMAPLUS Superior Performance<sup>8</sup>**

Contains a broad-spectrum antimicrobial treatment on the face and back of the panel that provides guaranteed resistance against the growth of mold and mildew.

**Grid Profile Options**

A	B	C	D	E	F	G	H
DX <sup>®</sup> /DXL™	DXW™	CENTRICITEE™ DXT	DX/DXL	CENTRICITEE DXT	FINELINE <sup>®</sup> DXF	FINELINE <sup>®</sup> 1/8 DXFF	CENTRICITEE DXT

**Physical Data/ Footnotes**

**Product literature**  
 Data sheet: SC2180  
**ASTM E1264 classification**  
 Type III, Form 2, Pattern CE  
**ASTM E84 surface burning characteristics**  
 Class A  
 Flame spread: 25  
 Smoke developed: 50

**Weight**  
 .78-1.03 lb./sq. ft.  
**Thermal resistance**  
 R-1.4 (5/8" panels)  
 R-1.7 (3/4" panels)  
**Maximum backloading**  
 See Warranty for details.  
**Maintenance**  
 Can be cleaned easily with a soft brush or vacuum.

**Footnotes**  
 1. Applies when USG acoustical ceilings recycling program is utilized.  
 2. Dependent on location; see Sustainability selector.  
 3. LR values are shown as averages.  
 4. For details, see Sustainability selector.  
 5. Panels have 15/16" routing.  
 6. Panels have 9/16" routing.  
 7. Mixing .50 and .60 NRC panels

in the same ceiling plane is not recommended  
 8. Panel face and back surfaces treated with a patented, broad-spectrum antimicrobial standard formulation that inhibits and retards the growth of mold and mildew. For details, see *Ceiling Systems Warranties and Limitations (SC2102)* and *CLIMAPLUS Ceilings Certification of Performance (SC2451)*.

